



2SD880

NPN SILICON TRANSISTOR


NPN EPITAXIAL TRANSISTOR

DESCRIPTION

The UTC **2SD880** is designed for audio frequency power amplifier applications.

FEATURES

- * High DC Current Gain: $h_{FE}=200(\text{Max.})(V_{CE}=5V, I_C=0.5A)$
- * Low Saturation Voltage: $V_{CE(SAT)}=1.0V(\text{Max.})(I_C=3A, I_B=0.3A)$
- * Complementary to 2SB834



ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
-	2SD880G-AB3-R	SOT-89	B	C	E	Tube
2SD880L-TA3-T	2SD880G-TA3-T	TO-220	B	C	E	Tube

Note: Pin Assignment: B: Base C: Collector E: Emitter

2SD880G-AB3-R (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) AB3: SOT-89, TA3: TO-220 (3) G: Halogen Free and Lead Free, L: Lead Free
---	---

MARKING

SOT-89	TO-220
1 2SD880G Data Code	1 UTC 2SD880 Lot Code Data Code L: Lead Free G: Halogen Free

■ ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Collector to Base Voltage			V _{CBO}	60	V
Collector to Emitter Voltage			V _{CEO}	60	V
Emitter to Base Voltage			V _{EBO}	7	V
Collector Current			I _C	3	A
Base Current			I _B	0.5	A
Power Dissipation	SOT-89	T _A =25	P _D	0.55	W
	TO-220			1.5	
	SOT-89	T _C =25		3	
	TO-220			30	
Junction Temperature			T _J	150	W
Storage Temperature			T _{STG}	-55~+150	°C







Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Emitter Breakdown Voltage	BV_{CEO}	$I_C = 50\text{mA}$, $I_E = 0$	60			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = 60\text{V}$, $I_E = 0$			100	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB} = 7\text{V}$, $I_C = 0$			100	μA
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	$I_C = 3\text{A}$, $I_B = 300\text{mA}$			1	V
Base-Emitter Saturation Voltage	$V_{BE(ON)}$	$V_{CE} = 5\text{V}$, $I_C = 500\text{mA}$			1	V
DC Current Gain	h_{FE}	$I_C = 500\text{mA}$, $V_{CE} = 5\text{V}$	100		200	
Current gain bandwidth product	f_T	$V_{CE} = 5\text{V}$, $I_C = 500\text{mA}$		3		MHZ

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.



Handsontec.com

We have the parts for your ideas

HandsOn Technology provides a multimedia and interactive platform for everyone interested in electronics. From beginner to diehard, from student to lecturer. Information, education, inspiration and entertainment. Analog and digital, practical and theoretical; software and hardware.



open source
hardware

HandsOn Technology support Open Source Hardware (OSHW) Development Platform.

Learn : Design : Share

www.handsontec.com

The Face behind our product quality...

In a world of constant change and continuous technological development, a new or replacement product is never far away – and they all need to be tested and qualified.

Many vendors simply import and sell without checks and this cannot be the ultimate interests of anyone, particularly the customer. Every part sell on Handsotec is fully tested. So when buying from Handsontec products range, you can be confident you're getting outstanding quality and value.

We keep adding the new parts so that you can get rolling on your next project.



www.handsontec.com

[Breakout Boards & Modules](#)



[Connectors](#)



www.handsontec.com

[Electro-Mechanical Parts](#)



www.handsontec.com

[Engineering Material](#)



www.handsontec.com

[Mechanical Hardware](#)



[Electronics Components](#)

P



www.handsontec.com

[Power Supply](#)



[Arduino Board & Shield](#)

Tools & Accessory



www.handsontec.com

[Tools & Accessory](#)